

Cigarette lighter torch

NiMH Button Cells

Cigarette Lighter Torch

A removable flashlight in the car cigarette lighter gives car manufacturers the possibility to extend brand awareness to the customer by focusing on increased comfort and multi useable standard accessories.

Battery challenge

Weight, reliability, thickness and optimum diameter is one of the most important features for removable flashlight as well as long shelf life respectively steady availability in charged state with high stability against overcharging. The battery must supply high discharge currents to drive the LED for about 1h usage time.

Technical solution:

NiMH Button Cells Technology

For more information, please visit our website:

<https://www.varta-ag.com/de/industrie/produktloesunen/nickel-metallhydrid>

Characteristics	3/V 600 HRT Battery
Voltage	3.6V (other voltages possible)
Dimension	Ø12mm x 7.3mm
Capacity	19mAh
Discharge Temperature range	-20°C to +85°C
Overcharge capability	0.6mA for 5 years @ RT
Weight	3g



Cigarette Lighter Battery

VARTA Microbattery's Ni-MH HRT batteries (Powerful85C family) offer rechargeable battery solutions with reliable power for supplying automotive light applications with an independent power source. Configurations: 3/V18HRT to 6/V18HRT

- wide temperature range from -20 to +85°C
- long lifetime – up to 10 years
- high reliability – by special sealing construction with new plastic materials
- high current capability
- design flexibility on voltage level from 1.2V to 6.0V
- design flexibility on battery shape side-by-side or stacked
- simple charging system continuous charging possible
- UL recognized cell
- environmentally friendly NiMH technology