

Data Sheet


Type Number 24276
Designation IEC LR44
System Manganese dioxide /
 Zinc / KOH - Electrolyte

Nominal Voltage 1,5 V
Typical Capacity C 155 mAh
 Load 5.6 kOhm, at 20°C down to 0.9 V

Weight (approx.) 2,0 g
Volume 0,51 ccm
Coding Date of Manufacturing
 Month/Year

Temperature Ranges min max.
Storage -10°C 65°C
Discharge -10°C 65°C*
 Low self-discharge with long operating life
 (<10% after 1 year of storage at +20°C).

Dimensions min max.
Diameter (Ø) 11,25 11,6
Height (A/B) 5,0 5,4

Typical Capacities (at 20°C)

Discharge Type	Load	End Voltage:	0.9 V
Continuous	5600 Ω	Time:	680 h
24h/d, 7d/w		Capacity [mAh]:	155
Current [μA]:		Energy [mWh]:	203

* Contact VARTA if the application is intended to be outside the range of -10°C to +65°C.

Information and contents in this data sheet are for reference purpose only.
 They do not constitute any warranty or representation and are subject to change without notice.
 For most current information and further details, please contact your VARTA representative.

VARTA Microbattery GmbH, VARTA-Platz 1, D-73479 Ellwangen/Jagst

Subject to change without prior notice!

Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-2553

Date of issue: 2022-10-12